

# EQUIPMENT SHEET

WATERWAY

TRAILING SUCTION HOPPER DREDGER



CONSTRUCTION / CLASSIFICATION		
Built by	Merwede Shipyard	
Year of construction	2001	
Classification	I № HULL № MACH № AUT-UMS Hopper dredger. Dredging within 15 miles from shore or within 20 miles from port. Dredging over 15 miles from shore with H.S. <= 2.5 m. Unrestricted navigation.	

## **FEATURES**

Shallow draught and large loading capacity.


Awarded "Ship of the year 2002": the most technically-innovative vessel built.

MAIN DATA	
Gross tonnage	5,393 GT
Length overall	97.70 m
Breadth	23.00 m
Moulded depth	7.00 m
Max. draught empty	4.04 m
Max. draught Int. load line	5.72 m
Max. draught dredging load line	6.58 m
Carrying capacity (D.W.)	7,192 t
Hopper capacity	4,906 m³
Suction pipe diameter	1 x 0.90 m
Max. dredging depth	28.00 m
Discharge systems	4 bottom doors/pump ashore/rainbow installation
Sailing speed loaded	12.5 kn
Total installed power	6,365 kW
Sand pump output	1,500 kW
Jet pump output	1,500 kW
Pump ashore output	2,760 kW
Propulsion power sailing	4,000 kW
Bow thruster	500 kW




#### **WATERWAY**

## TRAILING SUCTION HOPPER DREDGER



## **SIDE VIEW**



**TOP VIEW DECK LEVEL** 

#### Boskalis

PO Box 43 3350 AA Papendrecht The Netherlands T +31 78 69 69 000 royal@boskalis.com